

R-SERIES THERMAL WEAPON SIGHT



STANDARD ACCESSORIES

LaRue Mount, USB Charging Cable, USB Video Cable (Not with RS-24), Hard Case, Eyecup, Lens Caps, Lens Cleaner, AC Wall Charger, Quick Start Guide and User Manual.

The **FLIR® ThermoSight® R-Series Thermal Weapon Sight** is a compact, easy-to-use system that delivers rock-solid thermal imaging in zero light. This system is the ideal system because it detects heat energy, instead of visible light. Day or night, the body heat of animals will stand out against cooler backgrounds when seen through the R-Series scope.

The R-Series is built to perform under extreme conditions. This system combines outstanding image quality with an easy-to-use design. The scope optimizes images automatically using FLIR's own advanced image correction technology. And large, glove-friendly buttons - combined with a simple menu interface - give you access to every key setting in three clicks, or less.

MODEL:	RS-24 (1X)	RS-32 (1.25-5X)	RS-32 (2.25-9X)	RS-32 (4-16X)	RS-64 (1.1-9X)	RS-64 (2-16X)
RESOLUTION (VOX):	240X180	320X240	320X240	320X240	640X480	640X480
FRAME RATE:	30 HZ	60 HZ	60 HZ	60 HZ	30 HZ	30 HZ
LENS FOCAL LENGTH:	13 MM	19 MM	35 MM	60 MM	35 MM	60 MM
LENS HFOV:	20°	16°	9°	5°	18°	10°
FOCUS:	FIXED	FIXED	FIXED	MANUAL	FIXED	MANUAL
WEIGHT:	<1.8 LB	<1.8 LB	<1.8 LB	<2.4 LB	<1.8 LB	<2.4 LB
ELECTRONIC ZOOM:	N/A	UP TO 4X	UP TO 4X	UP TO 4X	UP TO 8X	UP TO 8X
COLOR PALETTES:	BLACK/WHITE/INSTALERT	BLACK/WHITE/SEPIA/IRON/RED/INSTALERT				
DISPLAY:	ACTIVE MATRIX LCD					
DISPLAY RESOLUTION:	640X480					
DIMENSIONS:	8" X 3.3" X 2.9"					
RETICLES:	DUPLEX, FINE DUPLEX, GERMAN					
RETICLE COLORS:	BLACK / WHITE / RED / GREEN					
DIOPTRER ADJUSTMENT:	+/-6					
OPERATING TEMPERATURE:	-4° TO 122°F (-20° TO 50°C)					
STORAGE TEMPERATURE:	-40° TO 140°F (-40° TO 60°C)					
BATTERY TYPE/LIFE:	INTERNAL LI-ION/>4 HOURS OF USE					
BATTERY CHARGING:	STANDARD USB INTERFACE WITH INCLUDED WALL CHARGER					
ON SCREEN SYMBOLOGY:	BATTERY CHARGE, E-ZOOM STATE					
WEAPON COMPATIBILITY:	MSR SEMI-AUTOMATIC UP TO .30 CAL.					
WARRANTY:	2 YEARS					