AN/PVS-22 NIGHT VISION WEAPON SIGHT



The Knight Vision® UNS Clip-on Weapon Sight, Type Classified as a MIL Spec AN/PVS-22, adds light intensification night vision to most rifles and day scopes. This product uses the latest high performance Gen III intensifier tube in a proven design, where the catadioptric lens provides high performance light collection with an effective f/1.2 in a light weight optic. The UNS is appropriate for front line rifles such as the M4 Carbine, M16A2/A4, M249, M14, and daysights with magnification up to 10X. The Knight Vision patented technology makes the product universal and assures the accuracy of your range-tested day scope boresight will not be degraded. When the UNS is added in front, your existing optic, eye relief, and cheek weld are undisturbed.



NIGHT VISION DEVICES

FEATURES

- **CLIP-ON NIGHT VISION SCOPE**
- SAIN CONTROL
- SIB®-SINGLE INTERCHANGE BATTERY
- **1 YEAR WARRANTY**
- W QUICK ATTACH/DETACH MOUNT



STANDARD ACCESSORIES

Operator's Manual, Soft Case, (1) AA Battery, Light Shroud and Lens Cleaning Kit.

SPECIFICATIONS

POWER SOURCE:	(1) AA OR 123 BATTERY
BATTERY LIFE:	EXCEEDS 24 HRS
MOUNT:	KAC MOUNT OR QUICK ATTACH/ DETACH TO MIL-STD-1913 RAIL OR EQUIVALENT
FOCUS RANGE:	10 METERS TO INFINITY
RECOGNITON RANGE:	700 M (HUMAN, 1/4 MOON)
MAGNIFICATION:	UNITY
BORE SIGHT:	WITHIN .5 MOA
WATERPROOF:	3 FT. FOR 4 HRS, 66 FT OPTIONAL
FINISH:	BLACK MATTE, CORROSION RESISTANT
CONTROLS:	PULL ON/OFF GAIN KNOB, FOCUS KNOB
WEIGHT:	1.75 LBS. (0.80 KG)
SIZE:	7.3″ (185 MM) LONG

AN/PVS-22 DATA SHEET - REV - JUNE 2016 NVDEVICES.COM » 610-395-9743 » SALES@NVDEVICES.COM Specifications subject to change without notice. Export of the commodities described herein is strictly prohibited without a valid export license issued by the U.S. Department of State Office of Defense Trade Controls prescribed in the International Traffic in Arms Regulation (ITAR), Title 22, Code of Federal Regulations, Parts 120-130. Approved for public release under International Traffic in Arms Regulations (ITAR) 22CFR 120.11