PVS-15 NIGHT VISION BINOCULAR



The **NVD PVS-15C Binocular** utilizes the same body and accessories as the Mil Spec AN/PVS-15, but built with commercial grade image intensifiers. A dual-tube goggle provides greater depth pereception which can be critical when performing surveillance and recognition missions.

The PVS-15C can be operated as a hand-held binocular or helmet mounted. Other features include single AA battery operation, Automatic Brightness Control (ABC), Built-in IR illuminator, submersible to 66 feet (20 meters), and IR light and low battery indicators.

The NVD PVS-15 utilizes MIL SPEC parts and accessories and is built with either Commercial, MIL GRADE or MIL SPEC Elbit Systems of America[®] GEN III Pinnacle Auto Gated image intensifier tubes.

FEATURES

FIVE YEAR WARRANTY

NIGHT VISION DEVICES

- SUBMERSIBLE TO 66 FEET
- SINGLE AA BATTERY USAGE
- **HIGH LIGHT CUTOFF**
- IR LED AND LOW BATTERY INDICATOR

SPECIFICATIONS

POWER SOURCE:	(1) AA-SIZE BATTERY
FOCUS RANGE:	11" TO INFINITY
EYEPIECE LENS EFL:	25MM
OBJECTIVE LENS EFL:	27MM
MAGNIFICATION:	ONE POWER (1X)
FIELD OF VIEW:	40 °
INTERPUPILLARY ADJUSTMENT:	52 TO 72MM
DIOPTER ADJUSTMENT:	-6 TO +2
WEIGHT (W/O BATTERIES):	25 OZ (690 G)
DIMENSIONS:	6.5" X 4.9" X 3.3"



STANDARD ACCESSORIES

Carrying Case, Lens Caps, Sacrificial Windows, Demist Shields, Lens Paper, (2) AA Batteries, Operator's Manual and Neck Cord

PVS-15 DATA SHEET - REV - FEBRUARY 2020 NVDEVICES.COM » 610-395-9743 » SALES@NVDEVICES.COM Specifications subject to change without notice. Export of the commodities described herein is strictly prohibited without a valid export license issued by the U.S. Department of State Office of Defense Trade Controls prescribed in the International Traffic in Arms Regulation (ITAR), Title 22, Code of Federal Regulations, Parts 120-130. Approved for public release under International Traffic in Arms Regulations (ITAR) 22CFR 120.11